Supporting Information for Marsh sedimentation controls delta top morphology, slope, and mass balance

K. M. Sanks^{1,2}, S. M. Zapp^{1,3}, J. R. Silvestre², J. B. Shaw¹^{*}, R. Dutt², and

K. M. Straub² [†]

¹University of Arkansas, Department of Geoscience, 340 N. Campus Drive, 216 Gearhart Hall, Fayetteville, AR 72701

²Tulane University, Department of Earth and Environmental Sciences, 6823 St. Charles Avenue, Blessey Hall, New Orleans, LA

70118

³Louisiana State University, Department of Oceanography and Coastal Sciences, 1002-Y Energy, Coast and Environment Building,

Baton Rouge, LA 70803

Contents of this file

- 1. Text S1 to S3 $\,$
- 2. Figures S1 to S3

Additional Supporting Information (Files uploaded separately)

1. Caption for Movie S1

^{*}Funded by the National Science

Foundation.

[†]Funded by the National Science

Foundation.

X - 2

Introduction The control experiment was conducted in the Tulane Sediment Dynamics Laboratory (PI: Kyle Straub) in 2018 and the treatment experiment was conducted in the Tulane Sediment Dynamics Laboratory (PI: Kyle Straub) in 2019. Here we provide additional information on the experimental design, deltaic sediment balance analysis, and delta hypsometry analysis.

Text S1.: Experimental design

We expand here on details of the data collection and marsh distribution. Because the treatment experiment was not fully automated, we paused the experiment for ~ 10 hours each night. During the progradation phase, overnight subsidence was tested by taking a LiDAR scan at the end of the day and beginning of the next day to observe changes in elevation. No detectable subsidence was observed when the experiments were paused overnight, thus pausing of the experiment did not impact the elevation data collected in comparison to the control.

We deposited the marsh sediment with about 50% accuracy. An average of 200 g of kaolinite was deposited per deposition cycle (2 hours), which is less than the average modeled deposition rate of 260 g/2-hrs (main text Figure 1d). The reasons for this were (1) compaction of the kaolinite in the sieve and (2) dampening of the ButtKickerTM signal that caused apparent uneven deposition through time. We mitigated this by switching the direction of the deposition every two hours (e.g., the first hour the sieve moved from left to right across the basin to deposit marsh and the second hour the sieve moved from right to left). We also re-calibrated the sediment dispenser after each depositional cycle. Though less accurate than anticipated, the deposition of marsh proxy altered the morphology and

surface processes of the delta. See SI Video 1 for a visual of the dispenser set-up and kaolinite deposition on the delta top.

Text S2: Deltaic sediment balance

We calculate the sediment volume balance for both the control and treatment experiments to directly compare the volume and rate of sediment storage throughout the delta. While this comparison is revealing, we are specifically interested in the influence of marsh sedimentation on delta volume balance; thus, we need to quantify the volume of the riverine and marsh sediment (kaolinite clay) in the treatment experiment throughout its entirety. Due to compaction of the marsh sediment, erosion, and deposition of both marsh and river sediment in the same area on the delta top, we cannot directly quantify the sediment accumulation using the LiDAR scans. Instead, we take advantage of the preserved stratigraphy to determine the marsh volume.

The resulting stratigraphy was split into two sections to acquire one cross-section along dip. Then the deposit was sectioned from distal to proximal along strike every 10 cm. Photographs were taken of each section and color image processing was used to obtain a marsh fraction roughly every 10 cm (Figure S1a).

Using this gridded stratigraphic data, we use Bayesian kriging techniques (Diggle & Ribeiro, 2007) to interpolate a pixel (5 mm x 5 mm) marsh fraction for the entire delta basin (Figure S1b and c). Bayesian kriging is a useful interpolation technique because it integrates data and model to predict values and uncertainty on those predicted values (Diggle & Ribeiro, 2007). Further, it is less likely to be biased than traditional interpolation techniques, producing a more accurate model (Diggle & Ribeiro, 2007). This method is also advantageous, as no information is required to set the parameters for the model.

Bayesian kriging determines all parameters (e.g., lambda) itself. We use the geoR package in R (Diggle & Ribeiro, 2001) and follow methods used in Sanks, Shaw, and Naithani (2020).

The semivariogram (Figure S1c) and associated interpolation model (Figure S1b) for the marsh fraction uses a constant mean ('cte') trend and a lambda of 1, which means that the data is normal and does not need to be transformed. The range of the data is 0.216 m, past which spatial autocorrelation is not observed. The bayesian spatial model with a constant mean trend results in an AIC of -1056.97. Leave-one-out cross-validation shows a good agreement between observed and predicted data, which is to be expected, as the stratigraphic data used in the model was collected with a high spatial density (see black points in Figure S1b). The data and code used to produce the interpolated marsh fraction are hosted in the Github and Zenodo repositories.

The volume balance for the different zones (e.g., fluvial, marsh window, delta top) was calculated using the final resulting stratigraphy. We define the fluvial region as the area that is above 5 mm relative to sea level (rsl) for at least 90% of the experiment to minimize the influence of marsh on sedimentation of this region in the treatment experiment. The marsh window is the area ≤ 5 mm rsl and ≥ -9 mm rsl for greater than 10% of the experiment. By using this criteria, the marsh window begins exactly where the fluvial zone ends (Figure S2). Finally, we define the delta top as the area that is ≥ -9 mm rsl for at least 50% of the experiment. This region then encompasses a smaller extent than the combined fluvial and marsh window area. However, we use this region to compare the average delta top area and volume of the two experiments.

$$V_T = (Z_{final} - Z_{initial}) * A_{pixel}, \tag{1}$$

where z_{final} is the pixel elevation of the last LiDAR scan, z_{initial} is the pixel elevation of the first LiDAR scan, and A_{pixel} is the area of one pixel (25 mm²). From there, we multiply by the interpolated marsh fraction (f_{m} ; -) to determine the marsh sediment accumulated (V_{m} ; mm³), given by:

$$V_m = f_m * V_T. \tag{2}$$

The clastic (riverine) sediment accumulated $(V_c; mm^3)$ is then:

$$V_c = V_T - V_m. aga{3}$$

Note that because the control experiment has no marsh deposition, V_m is 0 and V_c is simply equal to V_T . Refer to Table 2 in the main text for the zonal volume balance.

We compared the zonal mass balance for the fluvial area to a mass balance calculated using a moving average for the fluvial region. The moving window shows a sediment accumulation rate of 0.202 m^3 and 0.0655 m^3 for the control and treatment experiments, respectively. While this is about a 40% difference from the integrated zonal volume, both methods show a similar percent difference in volume between the two experiments. We integrated through time for each of the three zones (fluvial, marsh, and delta top) because even though the delta is in equilibrium, autogenic variability impacts short-term sediment depositon and resulting stratigraphy (i.e., the moving average does not account for longor short-term compactional subsidence) (Jerolmack & Sadler, 2007).

X - 6

The trapping efficiency (TE; %) is defined by:

$$TE = \frac{V_c}{V_D} * 100,\tag{4}$$

where V_D (a constant 0.660 m³) is the volume of clastic sediment delivered to the delta top and calculated by:

$$V_D = \left(\frac{flux}{\rho} * t\right) * 10^{-6},\tag{5}$$

where flux is the sediment being delivered to the system by the river (a constant 1406.14 g/hr), t is the entire run time of the experiment (560 hrs), and ρ is the bulk density of the clastic sediment (a constant 1.19 g/cm³), assuming an average 55% porosity (mean of cores taken from the control experiment) and a particle density of 2.65 g/cm³.

In Table 2 of the main text, we calculate two TE for the marsh window. The TE described by footnote a in Table 2 is the TE calculated using the clastic sediment delivered to the marsh window (V_{dm}) instead of the clastic sediment delivered to the delta top (V_D) :

$$V_{dm} = V_D - V_f,\tag{6}$$

where $V_{\rm f}$ is the total clastic sediment accumulated in the fluvial region.

Text S3: Delta hypsometry

We compare the hypsometry (elevation distribution) of the control and treatment experiments to the hypsometry of three vegetated and one non-vegetated field-scale deltas. In order to compare the experimental scale to the field scale, we non-dimensionalize the elevations of the delta top by dividing elevation by one average channel depth for the given system. The channel depths used are 15 mm for the experiments, 30 m for the Missississippi River Delta (MRD) and the Ganges Brahamaputra Meghna Delta (GBMD), 10 m for the Mekong River Delta, and 15 m for the Rio Grande River Delta. Notably, we see a

more similar hypsometric signature between the treatment and global deltas, as compared to the control. The treatment and gloabl deltas have >30% of their elevations between 0 and 0.5 channel depths above sea level. Specifically, the treatment experiment has 31%, MRD has 44%, GBMD has 64%, Mekong River Delta has 50%, and Rio Grande River Delta has 38% of elevations here. Comparatively, the control only has 17% of elevations in this 0 to 0.5 channel depths above sea level window. Rather, the control has a bi-modal distribution with peaks at 0.06 channel depths below sea level and 0.733 channel depths above sea level.

The elevation data for the field scale deltas was collected using ETOPO Global Relief Model (NOAA) in Google Earth Engine (GEE). GEE provides an interactive software, which we used to create polygons of the delta tops of three vegetated deltas (the Mississippi River Delta, Ganges Brahamaputra Meghna Delta, and Mekong River Delta), and one mostly unvegetated delta (the Rio Grande River Delta) (Figure S3).

X - 8

The polygons were created with the following rules. (1) We avoided locations that were greater than 3 channel depths above sea level and less than 1 channel depth below sea level, (2) we attempted to determine the entrance of the channel into the "delta top", and (3) we made sure to include the main distributary channels within the polygon area. While the areas were chosen somewhat arbitrarily, we tested different polygons for the same delta and did not observe a significant difference in the shape of the hypsometric curve or the peak elevation, thus we are confident in the patterns observed in main text Figure 3.

Movie S1. This video shows the marsh sediment dispenser in action. The sediment dispenser moves automatically from the center of one hexagon in the marsh window to the next. Once the sediment dispenser arrives, there is a short pause to wait for the dispenser to stop shaking. The kaolinite marsh proxy is then automatically dispensed and "rains down" on the delta top. The amount of sediment dispensed depends on the median elevation of the hexagonal grid cell.

References

Diggle, P. J., & Ribeiro, P. J. (2001). geoR: A package for geostatistical analysis.

- Diggle, P. J., & Ribeiro, P. J. (2007). Bayesian inference. In *Model-based Geostatistics* (pp. 157–198). New York, NY: Springer. Retrieved 2021-08-22, from https://doi.org/10.1007/978-0-387-48536-2_7 doi: 10.1007/978-0-387-48536-2_7
- Jerolmack, D. J., & Sadler, P. (2007). Transience and persistence in the depositional record of continental margins. Journal of Geophysical Research: Earth Surface, 112(F3). Retrieved 2021-10-12, from https://onlinelibrary.wiley.com/doi/ abs/10.1029/2006JF000555 doi: 10.1029/2006JF000555

Sanks, K. M., Shaw, J. B., & Naithani, K. (2020). Field-Based Estimate of the Sediment Deficit in Coastal Louisiana. *Journal of Geophysical Research: Earth Surface*, 125(8), e2019JF005389. Retrieved 2022-02-10, from https://onlinelibrary.wiley.com/doi/abs/10.1029/2019JF005389 (_eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1029/2019JF005389) doi: 10.1029/ 2019JF005389

:



Figure S1. (a) An along strike section of the treatment experiment at 1.1 m from the entrance channel. The targets on the left one-third of the image are spaced 10 cm apart and marsh fraction was collected for the entire deposit below each target. The red sediment is channel sand, white is channel floodplain, and brown is marsh. The tan sediment above and below the section is play sand and not part of the delta deposit. (b) The interpolated fraction of marsh sediment that is preserved in stratigraphy for the area above -9 mm relative to seal level for at least 10% of the experiment. The black dots represent the measured locations of marsh fraction and are roughly 10 cm apart. The raw data (black dots) was interpolated using a 5 mm x 5 mm grid (to match the resolution of the LiDAR data). (c) Semivariogram of stratigraphic marsh fraction for the treatment experiment.



:

Figure S2. (a and b) The yellow area represents the area above 5 mm (fluvial region) for at least 90% of the (a) control and (b) treatment experiments, while the turquoise area represents the area in the marsh window (-9 to 5 mm) for greater than 10% of the experiment.



Figure S3. Delta polygons. The satellite and topographic data for the field-scale deltas used in the hypsometric analysis and the corresponding polygons (blue) used to obtain elevation data. (a) The Mississippi River Delta located in Louisiana, USA. (b) The Ganges Brahamaputra Meghna Delta located in Bangladesh and West Bengal, India. (c) The Mekong River Delta located in Cambodia and Vietnam. (d) The Rio Grande River Delta located on the border of southeast Texas, USA and northeast Mexico. The scales vary on each map, but the north arrow and credits are the same for all.